





DESIGN & PERFORMANCE

Sleek, modern and built with durable stainless steel, the Roti-Roaster rotisserie combines elegance with functionality. Its "ROTISSERIE" screen-printed glass doors and powerful interior lighting beautifully showcase your products while they cook. Designed for efficiency, it features a front-load and rear door design, passthrough, for optimal performance.

Cleaning is effortless with removable accessories, interior panels, and a drip pan, ensuring convenience and hygiene. Engineered for high output, rapid cooking, and superior roasting, this rotisserie is built to last. Fully insulated with energy-efficient heating elements, it minimizes energy consumption while maximizing performance helping you save on costs without compromising quality.

ENERGY & COST-EFFICIENT K-GLASS

Designed for superior energy efficiency, the Roti-Roaster features insulated, double-glazed K-GLASS doors. The inner pane is coated with a specialized thin metal layer that regulates heat transfer, providing exceptional resistance to thermal radiation. This advanced design reduces energy consumption, lowers operational costs, and maximizes savings.

Additionally, K-GLASS minimizes heat emission in the kitchen, creating a cooler and more comfortable workspace for your team. The enhanced insulation also improves safety by preventing burns upon contact with the door surfaces, ensuring a secure cooking environment.

CONTROL PANEL



Standard (Default)

With 6 preset programs
+ manual control



Touch (Optional)

Multiple recipes + manual control (+ can add up to 99 programs)



FBPT8.760 + FBP8.76MSTO (optional base cabinet)




TECHNICAL CHARACTERISTICS

- Fully insulated with rock wool (Bio-soluble aluminum encapsulation)
- K-Glass thermal double glazing mounted on silicone seal (anti-scald front panel)
- · Control panel with 6 cooking programs
- Delivered with cooking baskets BALD720
- Enters auto hold at the end of the cooking cycle

ACCESSORIES (OPTIONAL)

BALD720	BAP720	PD720	PLC720	BCRA720	BV720
Basket for poultry	Small cuts basket	Vegetable tray	Cooking basket	Spatchcock spit	Chicken spit (fork)





SPECIFICATIONS

Weight	170kg		
Capacity of poultries	32		
Number of baskets	8		
Doors	2 double glazed door (1 anti-scald K.Glass door)		
Internal lighting	Halogen lamps protected by glass cover		
Power supply	3 Phase (230Δ400Y3N~)		
Electrical power	9.5kW		
Wire length	2m		
Temperature and Time control	Digital control or optional TOUCH Screen		
Cooking cycle alarm	Yes		
Internal presentation	Central axis, support and removable swing trays		



FBPT8.760 + FBP.PIED









Revised: March 2025











DISTRIBUTOR / AGENT

Rotisol S.A.S.

Zone industrielle La Trentaine, Avenue Gustave Eiffel 77507 Chelles cedex - FRANCE s.bennell@rotisol.com - Tel : +33 1 64 21 80 00 www.rotisol.com